DERWENT-ACC-NO: 1996-261151

DERWENT-WEEK: 199627

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Operating console for automobile electronic or electrical equipment - uses multi-function switch with single operating knob and microprocessor coupled to liquid crystal display for menu selection of required equipment

PATENT-ASSIGNEE: MOELLER J[MOELI]

PATENT-FAMILY:

PUB-NO PUB-DATE LANGUAGE PAGES

MAIN-IPC

d. ---

DE 29604717 U1 May 30, 1996 N/A 009

B60R 016/02

INT-CL (IPC): B60H003/00; B60J007/057; B60R001/00; B60R016/02; B62D001/04

ABSTRACTED-PUB-NO: DE 29604717U

BASIC-ABSTRACT: The operating console has a single operating knob which

depressed axially and pivoted in 4 different directions and an associated

switch lever for acting as a multi-function switch. The operating function is

selected using a microprocessor and a selection menu indicating each of

different equipments, provided by a liquid crystal display (2) in the field of

view of the driver, controlled by an on/off switch (5).

A memory button allows the selected settings for a given equipment to be stored in the microprocessor memory, with a memory call-up button for accessing the

stored settings.

ADVANTAGE - Designed for simple operation during driving.

CHOSEN-DRAWING: Dwg.1/4

TITLE-TERMS:

OPERATE CONSOLE AUTOMOBILE ELECTRONIC ELECTRIC EQUIPMENT MULTI FUNCTION SWITCH

SINGLE OPERATE KNOB MICROPROCESSOR COUPLE LIQUID CRYSTAL DISPLAY MENU SELECT

REQUIRE EQUIPMENT

DERWENT-CLASS: Q12 Q17 Q22 X22

02/26/2003, EAST Version: 1.03.0002

EPI-CODES: X22-X;

400

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1996-219694

VEHICULAR OPERATING DEVICE

Patent Number:

JP9315129

Publication date:

1997-12-09

JP9315129

Inventor(s):

MIYAZAWA YASUHIRO; KOBAYASHI TOMOO; TAKIGUCHI ISAO

Applicant(s)::

YAZAKI CORP

Requested Patent:

Application Number: JP19960167990 19960627

Priority Number(s):

IPC Classification:

B60H1/00; B60R11/00

EC Classification:

Equivalents:

Abstract

PROBLEM TO BE SOLVED: To permit a simple, accurate blind operation for driving and controlling various electric equipment mounted on a vehicle with no hindrance given to vehicle driving.

SOLUTION: A vehicular operating device 1 comprises a display 5 to display thereon a menu indication or a control indication for selecting the drive of various electric equipment mounted on a vehicle, a joystick 3 to select and determine a desired mode in the menu indication, and a controller 2 to change over the menu indication and determine a selected mode based on a selection signal V1 and a determination signal V2 supplied from the joystick 3. The joystick 3 is thus blindly operated through the watching of the display 5.

Data supplied from the esp@cenet database - 12